




SYNERGY TELECOM PVT

Budhella Vikas Puri New Delhi – 110018 (INDIA)

YH30/YH30C




YH31




YH60S/YH60CS




YH60U




YH32




YH34/YH34C



YH60HPR




YH61




YH30BL



YH36



YH60PR2




YH62



YH30TBO



YH60/YH60C/YH60X




















YH60TBO



YH60H



YH60HS/YH60CHS**YH72****YH652****YH656****YH63/YH63C****YH85/YH85C****YH65****YH657****YH70/YH70C****YH87****YH654****YH45/45C****YH70S/YH70CS****YH651****YH655****YH48/YH48C****YH48/YH48C****YH50C****YH27CG/YH27CGW****YH25/YH25C****YH48B2E****YH51C****YH29****YH26****YH55****YH49****YH90****YH21APN/YH21APS****YH74****YH27/YH27C****YH24APN/YH24APS****YH21CPN/YH21CPS**

YH23


Protective flexible vinyl insulator for 2 1/2 x 1 1/2 inch terminals.
Material: PVC
Color: black, red, yellow, green, blue, white

YH35

Protective flexible vinyl insulator for 3/8 inch terminals.
Material: PVC
Color: black, red

YH41A/YH41C

Jaw open 1.625" (41.3mm) max
Material: copper plated
Material: gold (YH41A), gold (copper) (YH41C), PVC insulator
Color: red, black
Rating: 200Amps or 400Amps

YH75K

Jaw open 0.313" (7.9mm) max
Material: silver-plated tip contacts, nylon housing
Rating: 10 Amps

YH11APN/YH11APS/YH11CPN/YH11CPS


Copper version
Jaw open 1.625" (41.3mm) max
Material: zinc plated steel (YH11A) or solid copper (YH11C)
Rating: 50Amps or 200Amps

YH58

Adhesive to pipe up to 1.38" max diameter
Material: zinc plated steel (YH58A) or solid copper (YH58C)
Rating: 50Amps

YH1028/YH102BK

YH1028BK has Kevlar insulated jaws and no copper shunt
Material: housing is nylon, jaw copper spring is steel, zinc plates
Length: 6.5" (165mm)
Color: red, black
Rating: 400Amps

YH78K

Jaw open 0.5" (12mm) max
Material: gold contacts
Rating: 10 Amps

YH13

Protective flexible vinyl insulator for 2 1/2 x 1 1/2 inch terminals.
Material: PVC
Color: black, red, yellow, green, blue, white

YH40A/YH40C


Jaw open 0.75" (19mm) max
Material: nickel plated steel (YH40A) or solid copper (YH40C)
PVC insulator
Color: red, black
Rating: 15Amps or 20Amps

YH102W

Material housing is nylon, jaw copper
Length: 6.5" (165mm)
Rating: 400Amps

YH-5869-B

Jaw open 0.52" (13.2mm) max
Use bed of nails to pierce insulation
Material: steel
Length: 2.4" (61mm)

YH33C

Jaw open 1.81" (45.7mm) max
Material: solid copper with copper lug
Rating: 300Amps

YH46A/YH46C

Jaw open 1.125" (28.6mm) max
Material: copper plated steel (YH46A) or solid copper (YH46C)
PVC insulator
Color: red, black
Rating: 50Amps or 70Amps

YHX15400


YHX15400
Jaw open 1.5" (38.1mm) max
Material: steel epoxy coated clips with copper plated jaws
Length: 6.5" (165mm)
Color: red, black
Rating: 200Amps

YH-5869-C

Jaw open 0.52" (13.2mm) max
Use circle of points to pierce insulation
Material: steel
Length: 2.4" (61mm)

YH-8078


YH-8078
Jaw open 1" (25.4mm) max
Use single spike to pierce insulation
Material: nickel-silver jaws, includes brass screw, nut, washer and bronze star washer
Length: 2.34" (59.4mm)

YH-33674

Jaw open 1" (25.4mm) max
Use single spike and bed of nails to pierce insulation
Material: nickel-silver jaws, includes brass screw, nut, washer and bronze star washer
Length: 2.61" (66.4mm)

YH8681


Protective flexible vinyl insulator for 2 1/2 x 1 1/2 inch terminals.
Material: PVC
Color: black, red, yellow, green, blue, white

YH-B417

Rubber insulator for YH-8078, YH-33674, YH-25182
Material: rubber
Color: red, black

YH-8783

Jaw open 1" (25.4mm) max
Use single spike and bed of nails to pierce insulation
Material: nickel-silver jaws, includes brass screw, nut, washer and bronze star washer
Length: 2.61" (66.4mm)

YH-33699

Jaw open 1" (25.4mm) max
Use single spike to pierce insulation
Material: nickel-silver jaws, includes brass screw, nut, washer and bronze star washer
Length: 2.61" (66.4mm)

YH-8783-2

Jaw open 1" (25.4mm) max
Use single spike and bed of nails to pierce insulation
Material: nickel-silver jaws, includes brass screw, nut, washer and bronze star washer, copper bowl, nickel plated
Length: 2.7" (68.5mm)

YH-25182

Jaw open 1.0" (25.4mm) max
Use bed of nails to pierce insulation
Material: nickel-silver jaws, includes brass screw, nut, washer and bronze star washer
Length: 2.34" (59.4mm)

YH-8783-3

Jaw open 1" (25.4mm) max
Use two spikes and bed of nails to pierce insulation
Material: nickel-silver jaws, includes brass screw, nut, washer and bronze star washer, copper bowl, nickel plated
Length: 2.7" (68.5mm)

YH-8099

Jaw open 1" (25.4mm) max
Use single spike to pierce insulation
Material: nickel-silver jaws, includes brass screw, nut, washer and bronze star washer
Length: 2.34" (59.4mm)



YH1001


Material: nickel plated steel clip
PVC-insulator
Rating: 5 Amp
Color: red/black/green, white/yellow

**YH1005**

Material: nickel plated steel clip
ABS-insulator
Rating: 5 Amp
Color: red & black

**YH1002**

Material: nickel plated steel clip
PVC-insulator
Rating: 5 Amp
Color: red/black/green, white/yellow

**YH1006**


Material: nickel plated steel clip
ABS-insulator
Rating: 10 Amp

**YH1003**


Material: nickel plated steel clip
PVC-insulator
Rating: 10 Amp
Color: red/black/green, white/yellow

**YH1007**

Material: nickel plated steel clip
ABS-insulator
Jaw open: 7mm max
Rating: 10 Amp
Color: red & black

**YH1004**

Material: nickel plated steel clip
ABS-insulator
Rating: 5 Amp
Color: red & black

**YH1008**


Material: nickel plated steel clip
ABS-insulator
Jaw open: 14.5mm max
Rating: 10 Amp
Color: red & black

**YH1009**


Material: nickel plated steel clip
nickel plated brass hex thread
PVC-insulator
Jaw open: 11mm max
Rating: 10 Amp
Color: red & black

**YH1103**

Material: nickel plated steel clip
PVC-insulator
Jaw open: 8mm max
Rating: 10Amp
Color: red & black

**YH1010**


Material: nickel plated steel clip
PVC-insulator
Jaw open: 11mm max
Rating: 10 Amp
Color: red & black

**YH1104**


Material: nickel plated steel clip
PVC-insulator
Jaw open: 15mm max
Rating: 20Amp
Color: red & black

**YH1101**

Material: nickel plated steel clip
PVC-insulator
Rating: 5Amp
Color: red/black/yellow, white/green

**YH1105**

Material: nickel plated steel clip
PVC-insulator
Jaw open: 13mm max
Rating: 20Amp
Color: red & black

**YH1102**


Material: nickel plated steel clip
PVC-insulator
Jaw open: 7.5mm max
Rating: 10 Amp
Color: red & black

**YH1106**

Material: nickel plated steel clip
PVC-insulator
Jaw open: 15mm max
Rating: 20Amp
Color: red & black

**YH1107**

Material: nickel plated steel clip
PVC-insulator
Jaw open: 22mm max
Rating: 30Amp
Color: red & black

**YH1203**

Material: nickel plated steel clip
PVC-insulator
Jaw open: 16mm max
Rating: 15Amp
Color: red & black

**YH1207**

Material: nickel plated steel clip
PVC-insulator
Jaw open: 26mm max
Rating: 30Amp
Color: red & black

**YH1211**


Material: Zinc plated steel clip
PVC-insulator
Rating: 200Amp
Color: red & black

**YH1108**

Material: nickel plated steel clip
PVC-insulator
Jaw open: 15mm max
Rating: 30Amp
Color: red, black/green

**YH1204**

Material: nickel plated steel clip
PVC-insulator
Jaw open: 18mm max
Rating: 25Amp
Color: red & black

**YH1208**

Material: Zinc plated steel clip
PVC-insulator
Jaw open: 40mm max
Rating: 200Amp
Color: red & black

**YH1252**

Material: nickel plated steel clip
PVC-insulator
2" length
Color: red & black

**YH1201**

Material: nickel plated steel clip
PVC-insulator
Jaw open: 17.5mm max
Rating: 5Amp
Color: red & black

**YH1205**

Material: nickel plated steel clip
PVC-insulator
Jaw open: 26mm max
Rating: 20Amp
Color: red & black

**YH1209**


Material: Zinc or nickel plated steel clip
PVC-insulator
Jaw open: 35mm max
Rating: 150Amp
Color: red & black

**YH1212**

Material: nickel plated steel clip
PVC-insulator
4" length
Color: red & black

**YH1202**

Material: nickel plated steel clip
PVC-insulator
Jaw open: 20mm max
Rating: 10Amp
Color: red & black

**YH1206**

Material: nickel plated steel clip
PVC-insulator
Jaw open: 26mm max
Rating: 50Amp
Color: red & black














**YH1210**


Material: copper plated steel clip
PVC-insulator
Jaw open: 45mm max
Rating: 250Amp
Color: red & black

**YH1213**

Material: nickel plated steel clip
PVC-insulator
6" length
Color: red & black




YH1214**YH1218****YH1240****YH1244****YH1215****YH1237****YH1241****YH1245****YH1216****YH1238****YH1242****YH1246****YH1217****YH1239****YH1243****YH1247****YH1248****YH1253****YH1258****YH1262****YH1249****YH1255****YH1259****YH1263****YH1250****YH1256****YH1260****YH1264****YH1251****YH1257****YH1261****YH1265**

YH1266


Material: nickel plated copper clip
Nylon insulator
Jaw open: 6mm max
2mm hole for connection
Color: red & black

YH1270


Material: nickel plated steel clip
Rating: 10 Amp

YH1267

Material: nickel plated steel clip
PVC insulator
Jaw open: 8mm max
Rating: 5 Amp
Color: red, black, green

YH1271

Material: cap and body is nylon,
spring: stainless steel,
contact: gold plated beryllium copper
Color: red/black
Rating: 600V, 3Amps

YH1268

Material: nickel plated steel clip
PVC insulator
Jaw open: 18mm max
Rating: 10 Amp
Color: red, black

YH1272


Material: cap and body is nylon,
spring: stainless steel,
contact: gold plated beryllium copper
Color: red/black
Rating: 600V, 3Amps

YH1269


Material: stainless steel clip
Jaw open: 6mm max
Rating: 5 Amp

YH1273


Material: cap and body is nylon,
spring: stainless steel,
contact: gold plated beryllium copper
Color: red/black
Rating: 600V, 3Amps

YH1274


Material: cap and body is nylon,
spring: stainless steel,
contact: gold plated beryllium copper
Color: red/black
Rating: 1000V, 10Amps

YH1278


Material: cap and body is nylon,
spring: stainless steel,
contact: gold plated beryllium copper
Color: red/black
Rating: 1000V, 15Amps

YH1275

Material: cap and body is nylon,
spring: stainless steel,
contact: gold plated beryllium copper
Color: red/black
Rating: 1000V, 10Amps

YH1279

Material: cap and body is nylon,
spring: stainless steel,
contact: gold plated beryllium copper
Color: red/black
Rating: 500V, 5Amps

YH1276


Material: cap and body is nylon,
spring: stainless steel,
contact: gold plated beryllium copper
Color: red/black
Rating: 1000V, 10Amps

YH1280

Material: nylon housing,
ABS housing,
spring: stainless steel,
contact: nickel plated brass,
contact: gold plated beryllium copper
Color: red/black, yellow/blue
Rating: 1000V, 20Amps

YH1277

Material: cap and body is nylon,
spring: stainless steel,
contact: gold plated beryllium copper
Color: red/black
Rating: 1000V, 15Amps

YH1281

Material: stainless steel needle,
ABS housing
Color: red & black
Rating: 500V, 10Amps

YH1219

Material: small clip, nickel plated steel with PVC insulators
wire: #22AWG copper with PVC insulation
Length: different length on demand
Color: includes 2 each: red, black, yellow, green, white
Rating: hands free testing at 300V, 5Amp

YH1223

YH60 clip with insulator to RJ11
with overmold strain relief test leads
Silicone wire with different length on demand

YH1227

2mm straight test probe of steel
shrouded 4mm banana right angle on the other end
PVC wire leads with different length on demand
Color: red & black

YH1231

Shrouded 4mm banana plug with steel test lead
Material: PVC or Silicone
Length: different length on demand
Rating: 20Amps, 1000V

YH1220

Material: middle clip, nickel plated steel with PVC insulators
wire: #22AWG copper with PVC insulation
Length: different length on demand
Color: includes 2 each: red, black, yellow, green, white
Rating: hands free testing at 300V, 7Amp

YH1224

Small safety alligator clips to shrouded 4mm banana plugs
Material: nickel plated steel clip, nylon housing
Banana plug: nickel plated brass body, nylon housing
Wire: 18AWG PVC wire
Length: different length on demand

YH1228

2mm straight test probe of steel
shrouded 4mm banana straight plug on the other end
PVC wire leads with different length on demand
Color: red & black

YH1232

YH783 clip to RJ11 with overmold strain relief test lead
Material: clip: PC-SL, insulator: PVC wire, Nylon, Spade terminal: Brass

YH1221

Material: big clip, nickel plated steel with PVC insulators
wire: #22AWG copper with PVC insulation
Length: different length on demand
Color: includes 2 each: red, black, yellow, green, white
Rating: hands free testing at 300V, 7Amp

YH1225

30A battery clip to socket lead
Material: nickel plated steel clip, PVC insulator
ABS car cigarette socket
PVC wire with different length on demand

YH1229

2mm straight test probe of steel
2mm rigid plug on the other end
PVC wire leads with different length on demand
Color: red & black

YH1233

Mini plunger to BNC Male with RG58 insulation
Material: BNC connector, gold plated center body, nickel plated, insulation: ABS
Wire: 20AWG stranding 41x0.12, PVC insulated 2.2mm OD
Plunger clip: metal contact is phosphorous bronze, insulation: nylon, one red, one black

YH1222

Material: clip, nickel plated steel with PVC insulators
wire: #22AWG copper with PVC insulation
Length: different length on demand
Color: includes 2 each: red, black, yellow, green, white
Rating: hands free testing at 300V, 5Amp

YH1226

400Amps battery clips with ring terminal
Material: ABS housing clip with copper plated steel teeth
PVC wire with different length on demand

YH1230

2pcs red & 2pcs black small alligator clips with threaded terminal
2pcs 2mm pin & 2pcs furcated terminal with thread
4pcs 4mm plug with thread
2pcs test leads with sockets
2pcs 2mm test probe of steel

YH1234

BNC Female breakout to stackable single banana plug
Material: BNC body, brass, nickel plated
Center contact: brass, gold plated
Insulation: ABS
Wire: 20AWG stranding 41x0.12, PVC insulated 2.2mm OD
Banana plug: body: brass, nickel plated, spring: beryllium copper, nickel plated, insulation: ABS, one red, one black

YH1282

Safety test lead one end with the insulated 2mm right angle banana plug and the other end with telescopic clip.
Nickel plated brass plug with nylon insulation.
Nickel silver clip with lead of male.
Highly flexible leads with different length on demand



YH1283

Test leads with 4mm stackable plug on both ends.
Nickel plated plug.
PVC or Silicone wire with different length on demand



YH1284

Test leads with 2mm stackable plug on both ends.
Nickel plated plug.
PVC or Silicone wire with different length on demand



YH1285

Test leads with 4mm stackable plug on both ends.
Nickel plated plug.
PVC or Silicone wire with different length on demand



YH1286

Safety test leads with 4mm stackable plug one end.
The other end with insulated 4mm stackable plug.
Nickel plated brass plug with red cap.
PVC or Silicone wire with different length on demand



YH1287

Insulated BNC male to two alligator clips.
Connected with the flexible RG58/50Q wire with different length on demand
Rating: CAT1 500V/CAT3 150V/3A



YH1288

BNC male to 2x4mm stackable plugs.
Connected with the flexible RG58/50Q wire with different length on demand
Rating: CAT1 500V/CAT3 150V/3A



YH1289

BNC male to 2x4mm stackable safety plugs.
Connected with the flexible RG58/50Q wire with different length on demand
Rating: CAT1 500V/CAT3 150V/3A



YH1290

2X 4mm stackable safety plugs to 2pos alligator clips.
Connected with the flexible RG58/50Q wire with different length on demand
Rating: CAT1 500V/CAT3 150V/3A



YH1291

BNC male to 2 mini test clips.
Connected with the flexible RG58/50Q wire with different length on demand
Rating: CAT1 500V/CAT3 150V/3A



YH8401

Material: 45# steel, PVC soft cover
material handle Shear stripping
function size accurate 4-0.5mm
hole stripping: 10-22AWG in-
adjustment Wire stripping
aperture adjustment spring
Surface treatment: anti-rust oil
Colors: red, yellow, blue, white



YH8406

Material: 45# steel, PVC insulator
handle ignition wire crimper Shear
screw, wire cutter, wire stripper
4-0.5mm hole stripping
10-22AWG in-
adjustment Surface treatment: anti-rust oil
Colors: red, yellow



YH8402

Material: 45# steel, PVC soft cover
material handle Shear stripping
function size accurate 4-0.5mm
hole stripping: 10-22AWG in-
adjustment Wire stripping
aperture adjustment spring
Surface treatment: anti-rust oil
Colors: red, yellow, blue, white



YH8407

Material: 45# steel, PVC insulator
handle ignition wire crimper Shear
screw, wire cutter, wire stripper
4-0.5mm hole stripping
10-22AWG in-
adjustment Surface treatment: anti-rust oil
Colors: red, yellow



YH8403

Material: 45# steel, PVC soft cover
material handle Shear stripping
function size accurate 4-0.5mm
hole stripping: 10-22AWG in-
adjustment Wire stripping
aperture adjustment spring
Surface treatment: anti-rust oil
Colors: red, yellow, blue, white



YH8408

Material: 45# steel, PVC insulator
handle wire stripper, wire stripping
adjustment, strong spring
Surface treatment: anti-rust oil
Colors: red, blue



YH8404

Material: 45# steel, PVC soft cover
material handle Shear stripping
function size accurate 4-0.5mm
hole stripping: 10-22AWG in-
adjustment Wire stripping
aperture adjustment spring
Surface treatment: anti-rust oil
Colors: red, yellow, blue, white



YH8409

Material: 45# steel, PVC insulator
handle ignition wire crimper Shear
screw, wire cutter, wire stripper
4-0.5mm hole stripping
10-22AWG in-
adjustment Surface treatment: anti-rust oil
Colors: red, yellow



YH8405

Material: 45# steel, PVC insulator
handle ignition wire crimper Shear
screw, wire cutter, wire stripper
4-0.5mm hole stripping
10-22AWG in-
adjustment Surface treatment: anti-rust oil
Colors: red, yellow



YH8410

Material: 45# steel, PVC insulator
handle ignition wire crimper Shear
screw, wire cutter, wire stripper
4-0.5mm hole stripping
10-22AWG in-
adjustment Surface treatment: anti-rust oil
Colors: red, black



YH8411

Material: 45# steel, PVC insulator
handle
Surface treatment: anti-rust oil
Colors: red, yellow



YH8421

Material: 45# steel, Non-slip
handle wire cutter
Surface treatment: anti-rust oil
Color: red, orange



YH8412

Material: 45# steel, PVC insulator
handle ignition wire crimper for
RG58 6U wire cutter
Surface treatment: nickel plated
Colors: red, black



YH8422

Material: steel and plastic
stripping range: 0.25-2.3mm
stripping diameter can be adjusted
automatically for different wire cross
sections Precise blade design
without damaging the conductor
cores During stripping, the wire is
held firm by clamping jaws



YH8413

Material: 45# steel, PVC insulator
handle ignition wire crimper for
RG58 6U wire cutter
Surface treatment: nickel plated
Colors: red, black



YH8426

Material: 45# steel, PVC insulator
handle Wire stripper, wire stripping
adjustment, strong spring
Surface treatment: anti-rust oil
Color: red, black



YH8414

Material: high-quality steel for
durability vinyl safety handles
Versatile multi-purpose electrical
tool Excellent for cutting wires and
stripping insulation Accommodates
from 22-10 AWG wire sizes
Adjuster, wire stripper, wire cutter,
ignition wire crimper Non-insulated
terminal crimper



YH8427

Material: carbon steel, Non-slip
PVC handle Multifunction for steel
wire high precise design of milling
edge Sharp edge for cutting wire
Surface treatment: nickel plated



YH8415

Material: zinc alloy, Non-slip
handle
Product description:
Sharp blade hardness: 45°-65°
Wire stripper quickly not hurt wire
core
Wire stripper range: 1.0, 1.8, 2.0,
2.8, 3.2mm single conductor
Surface treatment: spray paint



YH8428

Material: 45# steel, PVC insulator
handle Crimp for RG58U, RG59U,
Cut copper only
Color: blue handle



YH8429

Multi-Functional Modular Plug Crimper Professional modular crimping tool with the cutting and stripping function
 Could crimp all type of modular plug for BNC, BNC, 4P4C
 Material: PP+CS
 Crimping size: 6PSCRU12, 6PSCRU11, 6PSC4P4C
 Gross Weight: 250±5g
 Length: 150mm
 Handle color (Optional): Double color/Red
 Ratchet: No
 Packing: Blister

YH8433

Multi-Functional Modular Plug Crimper Professional modular crimping tool with the cutting and stripping function
 Could crimp all type of modular plug for BNC, BNC, 4P4C
 Material: PP+CS
 Crimping size: 6PSCRU15, 6PSCRU12, 6PSCRU11, 6PSC4P4C
 Gross Weight: 470±5g
 Length: 150mm
 Handle color (Optional): Green
 Ratchet: No
 Packing: Blister

YH8430

Multi-Functional Modular Plug Crimper Professional modular crimping tool with the cutting and stripping function
 Could crimp all type of modular plug for BNC, BNC, 4P4C
 Material: PP+CS
 Crimping size: 6PSCRU15, 6PSCRU12, 6PSCRU11, 6PSC4P4C
 Gross Weight: 420±5g
 Length: 150mm
 Handle color (Optional): Yellow
 Ratchet: No
 Packing: Blister

YH8434

Multi-Functional Modular Plug Crimper Professional modular crimping tool with the cutting and stripping function
 Could crimp all type of modular plug for BNC, BNC, 4P4C
 Material: PP+CS+AL
 Crimping size: 6PSCRU15, 6PSCRU12, 6PSCRU11, 6PSC4P4C
 Gross Weight: 420±5g
 Length: 150mm
 Handle color (Optional): Yellow
 Ratchet: No
 Packing: Blister

YH8431

Multi-Functional Modular Plug Crimper Professional modular crimping tool with the cutting and stripping function
 Could crimp all type of modular plug for BNC, BNC, 4P4C
 Material: PP+CS
 Crimping size: 6PSCRU15, 6PSCRU12, 6PSCRU11, 6PSC4P4C
 Gross Weight: 370±5g
 Length: 150mm
 Handle color (Optional): Blue
 Ratchet: Yes
 Packing: Blister

YH8435

Multi-Functional Modular Plug Crimper Professional modular crimping tool with the cutting and stripping function
 Could crimp all type of modular plug for BNC, BNC, 4P4C
 Material: PP+CS+AL
 Crimping size: 6PSCRU15, 6PSCRU12, 6PSCRU11, 6PSC4P4C
 Gross Weight: 420±5g
 Length: 150mm
 Handle color (Optional): Yellow
 Ratchet: Yes
 Packing: Blister

YH8432

Multi-Functional Modular Plug Crimper Professional modular crimping tool with the cutting and stripping function
 Could crimp all type of modular plug for BNC, BNC, 4P4C
 Material: PP+CS
 Crimping size: 6PSCRU15, 6PSCRU12, 6PSCRU11, 6PSC4P4C
 Gross Weight: 370±5g
 Length: 150mm
 Handle color (Optional): Yellow
 Ratchet: Yes
 Packing: Blister

YH8436

Multi-Functional Modular Plug Crimper 3 in 1 Multi-Functional network plug with cutting, stripping and crimping functions
 Material: PP+CS
 Crimping size: 6PSCRU15, 6PSCRU12, 6PSCRU11, 6PSC4P4C
 Gross Weight: 250±5g
 Length: 150mm
 Handle color (Optional): Double color/Red
 Ratchet: No
 Packing: Blister

YH5501

CASIO DC FEMALE CONNECTOR FOR 4+1 WIRE RT-4 DIA: 2.1*5.5mm

YH5005

RCA MALE CONNECTOR LONG TYPE FOR 4+1 WIRE RT-4

YH5002

CASIO DC FEMALE CONNECTOR (LONG TYPE) FOR 4+1 WIRE RT-4 DIA: 2.1*5.5mm

YH5006

BNC FEMALE CONNECTOR FOR 4+1 WIRE RT-4

YH5003

RCA FEMALE CONNECTOR FOR 4+1 WIRE RT-4

YH5007

CASIO DC MALE CONNECTOR FOR 4+1 WIRE RT-4

YH5004

CASIO DC MALE CONNECTOR FOR 4+1 WIRE RT-4

YH5008

BNC MALE CONNECTOR FOR 4+1 WIRE RT-4

YH3301

Insulator: ABS
 Body: brass
 Spring: beryllium
 Surface: nickel plated
 Solder connection
 Rated voltage/current: 30Vac-60Vdc/Max.19A

YH3305

Insulator: ABS
 Body: brass
 Spring: beryllium
 Surface: nickel plated
 Solder connection
 Rated voltage/current: 30Vac-60Vdc/Max.19A

YH3309

Insulator: ABS
 Body: brass
 Spring: beryllium
 Surface: nickel plated
 Solder connection
 Rated voltage/current: 30Vac-60Vdc/Max.19A

YH3313

Insulator: nylon
 Body: brass
 Spring: beryllium copper
 Surface: nickel plated
 Solder connection
 Rated voltage/current: CATII 60V/Max.32A

YH3302

Insulator: ABS
 Body: brass
 Spring: beryllium
 Surface: nickel plated
 Solder connection
 Rated voltage/current: 30Vac-60Vdc/Max.19A

YH3306

Insulator: ABS
 Body: brass
 Spring: beryllium
 Surface: nickel plated
 Solder connection
 Rated voltage/current: 30Vac-60Vdc/Max.19A

YH3310

Insulator: ABS
 Body: brass
 Spring: beryllium
 Surface: nickel plated
 Solder connection
 Rated voltage/current: 30Vac-60Vdc/Max.32A

YH3314

Insulator: nylon
 Body: brass
 Spring: beryllium copper
 Surface: nickel plated
 Solder connection
 Rated voltage/current: CATII 60V/Max.32A

YH3303

Insulator: ABS
 Body: brass
 Spring: beryllium
 Surface: nickel plated
 Solder connection
 Rated voltage/current: 30Vac-60Vdc/Max.19A

YH3307

Insulator: ABS
 Body: brass
 Spring: beryllium
 Surface: nickel plated
 Solder connection
 Rated voltage/current: 30Vac-60Vdc/Max.19A

YH3311

Insulator: nylon
 Body: brass
 Spring: beryllium
 Surface: nickel plated
 Solder connection
 Rated voltage/current: 30Vac-60Vdc/Max.32A

YH3315

Insulator: nylon
 Body: brass
 Spring: beryllium copper
 Surface: nickel plated
 Solder connection
 Rated voltage/current: CATII 60V/Max.32A

YH3304

Insulator: ABS
 Body: brass
 Spring: beryllium
 Surface: nickel plated
 Solder connection
 Rated voltage/current: 30Vac-60Vdc/Max.19A

YH3308



Insulator: ABS
 Body: brass
 Spring: beryllium
 Surface: nickel plated
 Solder connection
 Rated voltage/current: 30Vac-60Vdc/Max.19A

YH3312

Insulator: ABS
 Body: brass
 Spring: beryllium
 Surface: nickel plated
 Solder connection
 Rated voltage/current: 30Vac-60Vdc/Max.32A

YH3316

Insulator: PE
 Body: beryllium copper
 Spring: beryllium copper
 Surface: gold plated
 Solder connection
 Rated voltage/current: 30Vac-60Vdc/Max.19A

YH3317**YH3321****YH3325****YH3329****YH3318****YH3322****YH3326****YH3330****YH3319****YH3323****YH3327****YH3331****YH3320****YH3324****YH3328****YH3332****YH3333**

Closed screw type
Material: copper
Size: 4mm
Length: 45mm
Surface: 24K gold plated
Color: red/black plastic ring



Can accept bare wire or spades
Can accept 18 to 12 AWG speaker wires
Color coded/black/red rings for maintaining proper polarity
Secure, positive contact with binding posts
No soldering required

YH3337

Screw type
Material: copper
Size: 4mm
Length: 45mm
Surface: 24K gold & nickel plated
Color: red/black plastic ring



Can accept bare wire or spades
Can accept 18 to 12 AWG speaker wires
Color coded/black/red rings for maintaining proper polarity
Secure, positive contact with binding posts
Copper body construction and ferromanganese tips
No soldering required

YH3341

Material: Body: Brass
Spring: Beryllium copper
Surface: Nickel plated

**YH3345**

Material: Body: Brass
Spring: Beryllium copper
Surface: Nickel plated

**YH3334**

Screw type
Material: copper
Size: 4mm
Length: 45mm
Surface: 24K gold plated
Color: red/black plastic ring



Can accept bare wire or spades
Can accept 18 to 12 AWG speaker wires
Color coded/black/red rings for maintaining proper polarity
Secure, positive contact with binding posts
No soldering required

YH3339

Crimp type
Material: copper
Size: 2mm
Length: 45mm
Surface: 24K gold plated
Color: red/black plastic ring



Can accept bare wire or spades
Can accept 18 to 12 AWG speaker wires
Color coded/black/red rings for maintaining proper polarity
Secure, positive contact with binding posts
Copper body construction and ferromanganese tips
No soldering required

YH3342

Material: Body: Brass
Spring: Beryllium copper
Surface: Gold plated

**YH3346**

Material: Body: Brass
Spring: Beryllium copper
Surface: Nickel plated

**YH3335**

Screw type
Material: copper
Size: 4mm
Length: 45mm
Surface: 24K gold plated
Color: red/black plastic ring



Can accept bare wire or spades
Can accept 18 to 12 AWG speaker wires
Color coded/black/red rings for maintaining proper polarity
Secure, positive contact with binding posts
Copper body construction and ferromanganese tips
Some type of connector front and back
No soldering required

YH3338

Crimp type
Material: copper
Size: 2mm
Length: 45mm
Surface: 24K gold plated
Color: red/black plastic ring



Can accept bare wire or spades
Can accept 18 to 12 AWG speaker wires
Color coded/black/red rings for maintaining proper polarity
Secure, positive contact with binding posts
Copper body construction and ferromanganese tips
No soldering required

YH3343

Material: Body: Brass
Spring: Steel
Surface: Nickel plated

**YH3347**

Material: Body: Brass
Spring: Beryllium copper
Surface: Nickel plated

**YH3336**

Crimp type
Material: copper
Size: 4mm
Length: 35mm
Surface: 24K gold plated
Color: red/black plastic ring



Can accept bare wire or spades
Can accept 18 to 12 AWG speaker wires
Color coded/black/red rings for maintaining proper polarity
Secure, positive contact with binding posts
Copper body construction and ferromanganese tips

YH3340

Crimp type
Material: copper
Size: 2mm
Length: 35mm
Surface: 24K gold plated
Color: red/black plastic ring



Can accept bare wire or spades
Can accept 18 to 12 AWG speaker wires
Color coded/black/red rings for maintaining proper polarity
Secure, positive contact with binding posts
Copper body construction and ferromanganese tips

YH3344

Material: Body: Brass
Spring: Beryllium copper
Surface: Nickel plated

**YH3348**

Material: Body: Brass
Spring: Beryllium copper
Surface: Nickel plated



YH4301

Insulator: ABS
Body: brass
Surface: nickel plated
Rated voltage/current:
CATII 60V/Max.32A

YH4305

Insulator: ABS
Body: brass
Surface: nickel plated
Rated voltage/current:
30Vac-60Vdc/Max.18A

YH4309

Insulator: ABS
Body: brass
Surface: nickel plated
Rated voltage/current:
30Vac-60Vdc/Max.10A

YH4313

Insulator: ABS
Body: brass
Surface: nickel plated
Rated voltage/current:
30Vac-60Vdc/Max.24A

YH4302

Insulator: ABS
Body: brass
Surface: nickel plated
Rated voltage/current:
CATII 60V/Max.32A

YH4306

Insulator: ABS
Body: brass
Surface: nickel plated
Rated voltage/current:
30Vac-60Vdc/Max.24A

YH4310

Insulator: ABS
Body: brass
Surface: nickel plated
Rated voltage/current:
30Vac-60Vdc/Max.10A

YH4314

Insulator: nylon
Body: brass
Surface: nickel plated
Rated voltage/current:
30Vac-60Vdc/Max.10A

YH4303

Insulator: ABS
Body: brass
Surface: nickel plated
Rated voltage/current:
30Vac-60Vdc/Max.24A

YH4307

Insulator: ABS
Body: brass
Surface: zinc plated
Rated voltage/current:
30Vac-60Vdc/Max.24A

YH4311

Insulator: ABS
Body: brass
Surface: nickel plated
Rated voltage/current:
30Vac-60Vdc/Max.10A

YH4315

Insulator: ABS
Body: brass
Surface: nickel plated
Rated voltage/current:
30Vac-60Vdc/Max.10A

YH4304

Insulator: ABS
Body: brass
Surface: nickel plated
Rated voltage/current:
30Vac-60Vdc/Max.24A

YH4308

Insulator: ABS
Body: brass
Surface: zinc plated
Rated voltage/current:
30Vac-60Vdc/Max.10A

YH4312

Insulator: ABS
Body: brass
Surface: nickel plated
Rated voltage/current:
30Vac-60Vdc/Max.18A

YH4316

Insulator: nylon
Body: brass
Surface: nickel plated
Rated voltage/current:
30Vac-60Vdc/Max.15A

YH6601

12 volt car cigarette lighter plug
Brass metal inside and nylon
insulator

YH6605

Car cigarette lighter plug
Nickel plated brass metal and
ABS insulator

YH6609

Car cigarette lighter plug
Nickel plated brass metal and
nylon insulator

YH6613

Car cigarette lighter socket
copper metal inside and ABS
insulator

YH6602

12 volt car cigarette lighter socket
Brass metal inside and nylon caps

YH6606

Car cigarette lighter plug
Nickel plated brass metal and
ABS insulator
One spring or two spring

YH6610

Car cigarette lighter plug
Nickel plated brass metal and
ABS insulator
With 3-5A fuse and LED
(red/green)

YH6614

Car cigarette lighter socket
copper metal inside and ABS
insulator
With PVC cap

YH6603

Car cigarette lighter plug to socket
Brass metal and nylon insulator

YH6607

Car cigarette lighter plug
Nickel plated brass metal and
ABS insulator

YH6611

Car cigarette lighter plug
Nickel plated brass metal and
ABS insulator
With 3-5A fuse NO LED

YH6615

Car cigarette lighter socket
Metal housing with PVC insulator

YH6604

Car cigarette lighter plug
Nickel plated brass metal and
ABS insulator

YH6608

Car cigarette lighter plug
Nickel plated brass metal and ABS insulator

YH6612

Car cigarette lighter plug to two
socket
Nickel plated brass metal and
ABS insulator

YH6616

OBD2 female to 4 banana plugs
Solid molded female OBD-2 jack
(fits to passenger cars and
heavy trucks)
4 signal wires to 4 mm banana plug

Pin	Color	Signal	Color
1	Black	GND	Black1
2	Red	5V	Red1
3	Green	IG	Green1
4	Yellow	IG	Yellow1

YH6617



Auto cigarette lighter socket to DC plug
Highly flexible leads with different length on demand
Standard lead, PVC

YH6621



Auto cigarette lighter plug to DC plug
Highly flexible leads with different length on demand
Standard lead, PVC

YH6625



2 × 4mm safety test lead (1mm² J&P wire, L:100cm)
2 × 4mm test lead (1mm² J&P wire, L:100cm)
2 × test probe
2 × safety crocodile clips
2 × test clip
Packed in the tool bag

YH6618



Auto cigarette lighter socket to DC plug
Highly flexible leads with different length on demand
Standard lead, PVC

YH6622



Auto cigarette lighter plug to right angle DC plug
Highly flexible leads with different length on demand
Standard lead, PVC

YH6626



Maintenance and Repair Kit For Christmas & Miniature Light Sets
Twisting clip with RV snap connector and cables
16-Color bulbs
8-Flame bulbs
8-Multi-Color bulbs
8-Fuses
4-Marking Pins
Tweezers / Pull Wire
8 Volt Battery

YH6619



Auto cigarette lighter plug to DC plug
Highly flexible leads with different length on demand
Standard lead, PVC

YH6623



Auto cigarette lighter plug to DC plug
Highly flexible spring leads with different length on demand
Standard lead, PVC

YH6627



Multi-Function Jump Starter
Automobile emergency mobile power supply
Parts list:
1 × Switch cable
1 × Mobile phone connector cable
1 × notebook connector
1 × Home adaptor
1 × Car adaptor
1 × Jumper cable with battery clips
Trouble shooting
Size: 185*75*26mm
Output: 5V _ 2A 12V _ 2A 19V _ 3.5A
Input: 12V _ 1A
Full charging time: 4 hours
Starting current:200A
Peak current:400A
Operating temperature: 0℃-40℃

YH6620



Auto cigarette lighter plug to two insulated ring terminals
Highly flexible leads with different length on demand
Standard lead, PVC

YH6624



ECS to OBD-II adaptor
Highly flexible leads with different length on demand
Standard lead, PVC

YH6628



Choose the products from our catalogue and we will pack them into the tool box as you want. Suitable for the professional test kits.
Feature:
1. Special material to make the box that insure it can save in different working environment
2. Foam-rubber cushion protect the inside products.
3. Free logo space